

ARCHITECTURAL SPECIFICATIONS

LCD LOC II UNIVERSAL PROJECTOR MOUNT

The ceiling mount for the Projector shall be a **BMS LCD LOC SERIES UNIVERSAL SECURITY** mount, or equivalent, and shall be mounted where indicated on the plans. The mount will feature two interlocking steel trays that provide security as well as hold the projector steady and stable during maintenance. The mount must have DSA pre-approval. The mount shall not require the use of "security screws." It will feature a **high security, pick resistant, five wafer, cylindrical screw type KEY LOCK** to secure the two trays together. The mount will adjust, **WITHOUT THE USE OF TOOLS**, 15° +/- Tilt, Pitch, Roll and swivel 360°. The mount will be furnished with all the necessary hardware for mounting any projector as well as four flexible rubber disk with a metal insert and bonding material for added safety and security. The finish will be scratch resistant Projector Grey powder coat. It will be shipped fully assembled and can be readily installed to any 1-1/2" NPS pipe or fitting, permanently with the provided installation material. Installation shall be according to the manufacturer instructions.

- Two interlocking steel trays provide access and stability to projector during maintenance
- Cut-Outs are provided when necessary for easy access to filter and lamp
- Can attach to standard 1-1/2" pipe
- High security, pick resistant, five wafer, cylindrical screw type **key lock**
- DSA Approved
- 15° +/- Tilt, Pitch and Roll adjustments
- 360° Swivel
- 150 pounds weight capacity
- Low profile, only 4.5" high
- Flex Feet for safety and security
- Ships fully assembled

Weight: 10.5 lb
Shipping Weight: 11.1 lb
Maximum Load: 150 lb

